



SilkPerformer 2011

Release Notes

Borland[®]
(A MICRO FOCUS COMPANY)

 **MICRO**[®]
FOCUS

Micro Focus
575 Anton Blvd., Suite 510
Costa Mesa, CA 92626

Copyright © 2011 Micro Focus IP Development Limited. All Rights Reserved. Portions
Copyright © 1992-2009 Borland Software Corporation (a Micro Focus company).

MICRO FOCUS, the Micro Focus logo, and Micro Focus product names are trademarks or registered trademarks of Micro Focus IP Development Limited or its subsidiaries or affiliated companies in the United States, United Kingdom, and other countries.

BORLAND, the Borland logo, and Borland product names are trademarks or registered trademarks of Borland Software Corporation or its subsidiaries or affiliated companies in the United States, United Kingdom, and other countries.

All other marks are the property of their respective owners.

Contents

SilkPerformer Release Notes	4
What's New in SilkPerformer 2011	5
Start Page	5
Browser-Driven Load Testing Enhancements	5
Testing Web Applications for Mobile Devices	6
SilkPerformer Cloudburst Enhancements	6
Microsoft Silverlight Support	6
Microsoft Windows 7 and Microsoft Windows Vista UAC Compliancy	7
Project-Agent Configuration Enhancements	7
Agents Launched Under a Specific User Account	7
Configurable Remote Agent Java Settings	8
Enhanced Cross Loadtest Reports	8
Recording Rules with Custom Conversion	8
Technology Updates	9
Usability Enhancements	10
Tested Software	11
System Requirements and Prerequisites	15
Installation Instructions	17
Known Issues in SilkPerformer	19
General SilkPerformer Issues	19
Performance Explorer Issues	20
TrueLog Explorer Issues	21
SAPGUI Issues	22
Citrix Issues	23
Oracle Forms Issues	25
Web Issues	26
Browser-Driven Load Testing Issues	27
Database Issues	27
GUI-Level Testing Support	29
Resolved Issues	30
End of Support	32

SilkPerformer Release Notes

Version 2011

June 2011

This file contains important information that might not appear in the Help. Read this file in its entirety.

For information about installation, deployment, and licensing issues, refer to the [SilkPerformer Installation Help](#).

Navigate to supportline.microfocus.com for further assistance from Customer Care.

What's New in SilkPerformer 2011

SilkPerformer 2011 introduces significant enhancements and changes.

Start Page

When you start SilkPerformer Workbench, a new **Start Page** provides you with the ability to choose where you want to begin in the tool. You can start with any of the following options:

- Open a new or existing project.
- View or open recent projects or files.
- View a list of new features.
- Access a tutorial to get you started on using the software.
- View resource links to the Micro Focus Community and SupportLine to assist you with additional support.

This **Start Page** pane remains open until you close it or deselect the option to **Show page on startup**.

Browser-Driven Load Testing Enhancements

IE Compatibility Mode

A new **IE Compatibility Mode** setting has been added to the **Replay** tab of the **Profile Web (Browser Driven)** dialog box. This allows you to configure the version of Windows Internet Explorer (IE) that causes sending different HTTP headers to the server and rendering of the Web content. For example, IE9 as IE7 sends IE7 headers and renders as IE7.

Enhanced Navigation in Web Browser Windows

Several new features have been added to enhance navigation in Web browser windows for simulated actions performed during a test: you now have the ability to add a new tab while in a browser window, simulate file downloads to detect the saving actions of the user, and button actions and text entries on dialogs are analyzed.

In browser-driven load testing, you now have the ability to scroll vertically and horizontally when viewing a script. This can be useful when analyzing scripts and you need to easily find data at the bottom of the window. There are now two new functions (`BrowserGetScrollPos` and `BrowserSetScrollPos`) that support this scrolling functionality.

New Browser-Driven BDL Functions

The following new browser-driven Web load testing functions have been added to support these new features:

- `BrowserCreateWindow`
- `BrowserDlgSetButton`
- `BrowserDlgSetText`
- `BrowserDlgStop`
- `BrowserExecuteJavaScript`
- `BrowserFileDownload`
- `BrowserGetIEMode`

- `BrowserSetIEMode`
- `BrowserGetScrollPos`
- `BrowserSetScrollPos`

Testing Web Applications for Mobile Devices

SilkPerformer fully supports performance testing of mobile web applications. It offers simulation capabilities for a variety of mobile devices, such as Android, iOS, and Blackberry devices, but other mobile browsers can also be simulated with custom profiles.

An interesting and important simulation parameter for mobile Web application testing is the bandwidth limitation. This option is not significant for usual Web testing via PCs due to the fast wired (broadband) internet connections, however for real world simulation of mobile devices it makes a real difference to set the bandwidth to particular limits. SilkPerformer offers many standard bandwidth limitation settings used in the mobile world, such as EDGE, HSDPA, or LTE.

SilkPerformer Cloudburst Enhancements

Cloud-Based Region Summary Reports

Region summary reports gather cloud-based load test measures across geographic regions. When load tests use cloud-based agents, SilkPerformer captures region-specific data for each cloud region (and for project agents, if used). Region summary reports are similar to baseline reports. Region summary report files carry the file extension `.rsr` and are stored in the results directory.

To view region summary result nodes, expand the **Region Summary Reports** node on the **Results** tab following a load test.

Region Comparison Reports

Region comparison reports compare cloud-based load test measures across geographic regions, with results from different regions compared side by side, one region per column.

A number of options are available for configuring region comparison reports. Total test results, which contain measure results from all regions, can be compared side by side with region-specific measure results. Alternatively, region comparison reports can be configured to include data only from select combinations of individual region results.

Additional regional results can be added to an existing report (by dragging and dropping individual region nodes from the **Explore** tab into the report) and total results can be added to an existing report (by dragging and dropping the **Client Measures** node into the report).

Microsoft Silverlight Support

SilkPerformer now supports Microsoft Silverlight, versions 4 and 5.

The workflow for testing Microsoft Silverlight browser-based applications with SilkPerformer is the same as the workflow used for testing Web-based applications, with the following exception:

- On the **Workflow - Outline Project** dialog, you must select `Silverlight` under the **Web browser** node.

Microsoft Windows 7 and Microsoft Windows Vista UAC Compliance

In support of User Account Control (UAC) on Microsoft Windows 7 and Microsoft Windows Vista systems, SilkPerformer offers an enhanced directory structure that promotes system security. Specifically, the **Working** directory has been deprecated and all child directories of the **Working** directory have been migrated to other areas of the directory structure.



Note: UAC compliancy has also been introduced for folder structures in TrueLog Explorer, Performance Explorer, .NET Explorer, and Java Explorer.

UAC is a Microsoft Windows technology that promotes system security by limiting the privileges of application software to standard-user levels. Users have the option of explicitly granting administrator-level privileges to applications that are deemed trustworthy.

New SilkPerformer Folder in My Documents

The **Custom Data**, **Custom Include**, and **Projects** folders now appear in **My Documents** by default. Shortcuts to the **Data**, **RecordingRules**, and **SampleApps** directories, which are now located within the **Public Documents/Shared Documents** directories, are also included in **My Documents**.

New RecordingRules Folder

Recording rules are no longer saved to the **Include** folder. They are now saved to the new **RecordingRules** folder.

Temporary Files

Temporary files are now saved to the application data directories (for example, %LOCALAPPDATA%\SilkPerformer 2011\Temp) of the current user and all users.

Project-Agent Configuration Enhancements

The **Configure Project Agents** dialog now includes both an **Available Agents** pane, which lists all agents that are available for configuration and inclusion in your project, and a **Project Agents** pane, which lists the agents that are configured and available for your project.

Enhancements include the following:

- Double-click an agent name to move the agent from one pane to another.
- Place your cursor over an agent name to display that agent's system and agent-version details in a tool tip.
- Foreign agents (indicated by a question mark icon) listed in the **Project Agents** pane can be added to the agent pool by right-clicking them and choosing **Add to Agent Pool**.

Agents Launched Under a Specific User Account

Now you have the ability to specify particular user account credentials in a central location to be used for all agents. This feature allows agents to be launched under a specific user account rather than the default system account.

A new **Advanced** tab has been added to **System > Settings > Agents**. This tab offers a new check box **Use particular user account** that you can select and specify the username and password credentials with permission to launch the agents to test.

Configurable Remote Agent Java Settings

You can enter filepath information regarding the location of the JRE or JDK on remote agent machines independent of the location of the Java home settings on the workbench machine. This means that you do not need to maintain identical Java home settings between your workbench and remote-agent machines. You can even opt to install only a JRE on remote machines without a JDK.

A new **Remote** tab has been added to **System > Settings > Java**. This tab offers three controls: **Java home**, **Classpath**, and **Command line options**. These controls mirror the workbench Java controls that are on the **General** and **Advanced** tabs at the same location.

There is a corresponding profile settings tab at **System > Active Profile > Java** that pulls its initial values from the remote-agent settings at **System > Settings > Java**. It is the values on the active profile tab that are actually applied to remote-agents at test time.

Enhanced Cross Loadtest Reports

Now Available for SilkPerformer Results

Cross loadtest reports can now be generated for SilkPerformer test results via Silk Performance Explorer. Previously it was only possible to generate cross loadtest reports for results downloaded from SilkCentral Test Manager.

To generate a cross loadtest for SilkPerformer test results, click the **New Cross Loadtest Report** button on the Silk Performance Explorer toolbar. Then drag measurements (local results) from the **Explore** menu tree into the report.

Cloud-Based Region Measures

SilkPerformer cloud-based region measures can also now be integrated into cross loadtest reports. To add a region measure to an existing cross loadtest report, drag a region measure (**Region** node) from the **Explore** menu tree into the report.

Improved Layout for User Groups

The layout of cross loadtest reports has been improved so that when you have more than a single user group, the summary of all user groups appears first in the list (not last, as was previously the case).

Recording Rules with Custom Conversion

You can write your own custom conversion function and specify this conversion function in a recording rule. The conversion function is contained in a native DLL file (programmed in C/C++). Within the conversion function, the value in the parsing rule is converted using the specified function, while the parsing function only parses the original value.

For example, when values are returned by the server in a double format they are sent by the client in an integer format. Therefore, a simple parsing rule will not find any matches in the script. However by applying a custom conversion function that converts the integer to a double format, the parsing rule is able to find the expected matches again.

To learn about the structure and syntax of recording rules, and to see more information about the custom conversion feature, refer to *SilkPerformer Advanced Concepts*.

Technology Updates

SilkPerformer2011 supports the testing of the following latest technologies and applications:

Oracle Forms and Oracle Applications

SilkPerformer now supports Oracle Forms 10g, 11g, and Oracle Applications 12i.

Microsoft Silverlight

SilkPerformer now supports record and replay of Microsoft Silverlight applications.

WCF and .NET 4.0 Assemblies

.NET Explorer now supports testing of WCF Web Services and .NET 4.0 assemblies. Additionally, SilkPerformer's .NET API has been updated to also support .NET 4.0 assemblies.

SAPGUI 7.20

SilkPerformer now supports SAPGUI 7.20.

Monitoring WebLogic Server 11.x

In addition to long-standing monitoring support for WebLogic Server versions 8.x, 9.x, and 10.x with Performance Explorer, SilkPerformer now supports the monitoring of WebLogic Server 11.x via JMX.

Support for WebLogic Server 11.x includes the following:

- WebLogic Server 11g (10.3.1)
- WebLogic Server 11gR1 PS1 (10.3.2)
- WebLogic Server 11gR1 PS2 (10.3.3)
- WebLogic Server 11gR1 PS3 (10.3.4)



Note: Before you can monitor Oracle WebLogic Application Server, some server-side configurations must be performed. See Performance Explorer Help for full details.

Monitoring Oracle Database With Perfmon

In addition to Performance Explorer's long-standing support for Oracle Database monitoring via V \$SYSSTAT, you can now monitor Oracle Database via Perfmon. Numerous Oracle Counters can now be added to Windows Performance Monitor.

Monitoring the Latest Versions of SilkCentral Test Manager

Performance Explorer now includes predefined data sources for monitoring the application server and front-end server of SilkCentral Test Manager 2008, 2008 R2, 2009, 2009 R2, 2010, 2010 R2, and 2011.

Monitoring the Latest Versions of Internet Information Services (IIS)

Performance Explorer has been updated to include predefined data sources for monitoring the currently supported versions of IIS: Internet Information Services (IIS) 5.1, 6.0, 7.0, 7.5

Monitoring the Latest Versions of Microsoft SQL Server

Performance Explorer has been updated to include predefined data sources for monitoring the currently supported versions of Microsoft SQL Server: Microsoft SQL Server 7.0, 2000, 2005, 2008, 2008 R2

Updated Browser List for Simulating Network Environments

The list of available browsers for the simulated network environment in the project profile settings has been enhanced to include Windows Internet Explorer 9.0, Mozilla Firefox 4.0, iPhone, iPad, Android, and Blackberry. Technologies that are no longer supported (Phone.Com Generic Toolkit 4.0, Nokia Toolkit 1.3, i-Mode) have been removed from the list.

Usability Enhancements

Usability enhancements have been implemented throughout SilkPerformer:

Enhanced Network-Simulation Settings

The network-simulation profile settings have been modified to simplify the configuration of the bandwidth simulation. You can now select from a list of connection types, like for example GPRS, WLAN, Modem, or DSL, and then modify the upstream and downstream speeds with slider controls.

SilkCentral Test Manager Integration Enhancements

When uploading test results to SilkCentral Test Manager, you can now check the **Automatically open Upload path on finish** check box to automatically start Test Manager and go directly to the selected test definition.

Additionally, the full name of a load test is now visible and customizable in Test Manager. When downloading results from Test Manager, SilkPerformer and Performance Explorer display the name of a test as it has been defined in Test Manager.

Tested Software

This section lists the software with which SilkPerformer has been tested.

System Area	Tested With
Operating systems	<ul style="list-style-type: none"> • Microsoft Windows XP with Service Pack 3 • Microsoft Windows XP 64bit with Service Pack 3 • Microsoft Windows Server 2003 with Service Pack 2 • Microsoft Windows Server 2003 64bit with Service Pack 2 • Microsoft Windows Vista with Service Pack 2 • Microsoft Windows Vista 64bit with Service Pack 2 • Microsoft Windows Server 2008 with Service Pack 2 • Microsoft Windows Server 2008 64bit with Service Pack 2 • Microsoft Windows Server 2008 R2 • Microsoft Windows Server 2008 R2 with Service Pack 1 • Microsoft Windows 7 32bit • Microsoft Windows 7 64bit • Microsoft Windows 7 32bit with Service Pack 1 • Microsoft Windows 7 64bit with Service Pack 1
Web browsers	<ul style="list-style-type: none"> • Windows Internet Explorer 6.0, 7.0, 8.0, 9.0 • Opera 8.5.1, 9.2 • Mozilla Firefox 3.0 or later • Google Chrome
Terminal emulation support	<ul style="list-style-type: none"> • AttachMate Extra 8 • AttachMateWRQ 13.0 • Distinct IntelliTerm 8.1 • Ericom Powerterm Pro v8.8.1 • HummingBird_Exceed 11.0 (hooking via socks proxy) • JProtector 4.5.2.0 • MochaSoft 5.3 (hooking via socks proxy) • NetTerm 5.1.1 • Nexus Terminal 5.3 • PassportPC2Host 3 • Quick3270 3.73 • Rumba 7.4 • Rumba 8 • SDI TN3270 Plus v2.4 • SecureCRT 1.0 • TeraTermPro 2.3 • TN5250_sourceforge 0.17.3 • TNBridge

System Area	Tested With
ERP/CRM support	<p>SAPGUI Clients:</p> <ul style="list-style-type: none"> • SAPGUI client 620, Patches 44, 50, 66 (recommended), and 20 • SAPGUI client 720 • SAPGUI client 710 <p>PeopleSoft Systems: PeopleSoft 8.0, 8.3, 8.4, and 8.8</p> <p>Siebel Systems:</p> <ul style="list-style-type: none"> • Siebel 6.3 using MS SQL Server • Siebel 6.3 using IBM DB2 • Siebel 6.3 using Oracle • Siebel 7 • Siebel 8.0, 8.1 <p>Clarify Systems: Clarify eFrontOffice 8, 10</p> <p>Remedy Web ARS: Remedy Web ARS 6.3, 7.0, 7.0.1, 7.1, 7.5, 7.6</p>
Citrix support	<p>Citrix Clients:</p> <ul style="list-style-type: none"> • Citrix XenApp Client 11, 11.2, 12.0 • Citrix Web Interface 5.1, 5.2, 5.3 <p>Citrix Servers:</p> <ul style="list-style-type: none"> • Citrix Presentation Server 4.0, 4.5 • Citrix XenApp 5.0, 6.0 <p>Operating Systems:</p> <ul style="list-style-type: none"> • Microsoft Windows XP • Microsoft Windows Server 2003 • Microsoft Windows Server 2008
Oracle Forms support	<ul style="list-style-type: none"> • Oracle Forms 6i, 9i, 10g, 11g • Oracle Applications 11i, 12i
SOAP support	<ul style="list-style-type: none"> • Microsoft SOAP Toolkit 2.0 Service Pack 2 (SP2), Internet Information Server 5 • Apache-SOAP Version 2.1, TOMCAT Version 3.1
Web Service Support	<ul style="list-style-type: none"> • Axis 1.x • Axis2 1.4, 1.5 • GlassFish Metro 1.5
Database support	<ul style="list-style-type: none"> • IBM Universal Database Systems 5.2, 6.1, 7.1 • Microsoft SQL Server 7.0, 2000, 2005, 2008, 2008 R2

System Area	Tested With
	<ul style="list-style-type: none"> • Oracle7 Server Release 7.3.2.2.1 • Oracle8 Enterprise Edition Release 8.0.3.0.0, 8.0.5.0.0 • Oracle8i Release 8.1.5, 8.1.6, 8.1.67 • Oracle Database 10g Release 2 • Oracle Database 11g Release 2 • Sybase SQL Anywhere Network Server 5.5.04
Corba support	<ul style="list-style-type: none"> • BEA WebLogic Enterprise 5.0.1, 6.0, 6.1 • VisiBroker Java/C++ 3.x, 4.x, 5.x, 6.x • Inprise Application Server 4.0 • Iona Orbix • IBM WebSphere 3.5, 4.x, 5.0 • Iona iPortal Application Server 1.1
TUXEDO support	<ul style="list-style-type: none"> • BEA TUXEDO Server 6.3, 6.4, 7.0, 7.1, 8.0, 9.0 • BEA WebLogic Enterprise 4.2
Jolt support	BEA Jolt 1.1 (including BEA TUXEDO Server 6.4), 1.2
Java support	<ul style="list-style-type: none"> • Java Runtime Environment 1.2.2: classic and hotspot 1.0 • Java Development Kit 1.4, 1.5, 1.6, 1.7 • IBM Java Development Kit 1.3 • Eclipse 3.2, 3.3, 3.4, 3.5, 3.6
.NET support	<ul style="list-style-type: none"> • Microsoft .NET Framework 1.0, 1.1, 2.0 • Microsoft .NET Framework runtime 4.0 • Microsoft Visual Studio 2008 and 2010 • WCF Web Services
Rich Internet applications (Web 2.0)	<ul style="list-style-type: none"> • Microsoft Silverlight 4, 5 • Adobe Flex 2, 3, 4 • Google Web Toolkit • ExtJS 3 • Eclipse RAP • script.aculo.us
SNMP support	<ul style="list-style-type: none"> • SNMPv2-MIB • RFC1213-MIB • RDBMS-MIB • ORADB-MIB • httpServer-MIB • ftpServer-MIB • SUN-MIB • BEA-WEBLOGIC-MIB • APPSRV_MIB (NetDynamics) • SQUID-MIB

System Area	Tested With
Proxy servers for firewall tunneling	 Note: To find RFCs and vendor MIBs on the Web, visit The Internet Engineering Task Force . <ul style="list-style-type: none"> • Microsoft Proxy Server 2.0 • Netscape Proxy Server 3.5 (due to a defect in Netscape Proxy Server, HTTP tunneling is not supported) • WinGate 4.0.1 • Squid 2.3.STABLE4 (LINUX) • Squid 2.4 STABLE3 (LINUX) • Dante 1.1.6 (LINUX)
Source Code Control Integration (SCCI) support	<ul style="list-style-type: none"> • StarTeam (with SCC Integration patch) 2005 R2, 2006, 2008 • Microsoft Visual SourceSafe 6.0c, 6.0d, 2005 • Merant Version Manager 8.0.2.0

System Requirements and Prerequisites

The following tables identify the system requirements for installing and running SilkPerformer. For details about SilkPerformer performance and scalability, see the *Performance and Scalability Matrix*.

Hardware Requirements

To run the SilkPerformer agent software, or both controller and agent software, and to use the full potential of SilkPerformer to run large-scale load-tests, your system must meet the following minimum requirements:

Table 1: Load Testing

System Area	Requirement
Processor	Pentium IV or equivalent CPU
RAM	512 MB recommended minimum 1 GB recommended
Virtual memory	Three times as much virtual memory as RAM
Hard disk space	650 MB for controller software installation. 170 MB for agent-only installation. Depending on the size of your load tests, make sure you have enough space on your hard disk for result files.
Network	Windows network with TCP/IP (when using remote SilkPerformer Agent computers)
Network adapter	10 MBit recommended minimum fast Ethernet recommended

To use SilkPerformer for traffic recording purposes, scripting, and monitoring, your system must meet the following minimum requirements:

Table 2: Recording, Scripting, and Monitoring

System Area	Requirement
Processor	Pentium IV or equivalent CPU
RAM	256 MB
Hard disk space	440 MB
Network	TCP/IP

Software Requirements

To install and run SilkPerformer, your system requires a minimum set of software components:

The specific components that are required vary based on installation type. For example, to run SilkPerformer Java Explorer, your system must be equipped with either of Java Development Kit 1.4, 1.5, 1.6, 1.7. Download components from their respective vendors' Web sites.

- Microsoft .NET Framework 4.0
- Windows Internet Explorer 7.0 or 8.0 for browser-driven recording

- Adobe Acrobat Reader to view documentation
- Citrix XenApp Client 11, 11.2, 12.0 or Citrix Web Interface 5.1, 5.2, 5.3 to test Citrix applications
- Java Development Kit 1.4, 1.5, 1.6, 1.7 to test Java applications with Java Explorer

Installation Instructions

For information about installation, deployment, and licensing issues, refer to the [SilkPerformer Installation Help](#).

Licensing Information

SilkPerformer2011 needs a new 8.3 license. If you want to run a previous version of SilkPerformer during the upgrade process to version 2011, you may keep your old licenses for a period of 90 days.

SilkPerformer's licensing model is based on Virtual User Types (VUser Types). The available VUser Types *Web*, *Standard*, and *Premium* include the following SilkPerformer application types:

VUser Type	Application Type
Web	Web Browser-Driven
	HTTP(S) (Web browser low level)
	HTTP(S)/HTML (Web browser high level)
	HTTP(S)/XML (Web services, SOAP)
	SAP NetWeaver
	WebDAV (MS Outlook Web Access)
	Email (SMTP/POP)
	FTP
	TCP/IP
	UDP
	i-Mode (HTTP)
	AMF0/AMF3/FLEX
	DLL Interface
	Standard
.Net Add-On	
Java Add-On	
DB2-CLI Add-On	
OCI Add-On	
ODBC Add-On	
Visual Basic Add-On (Framework)	
Directory server (LDAP)	
CORBA Add-On	
Premium	
	GUI Level Testing
	Remedy Web ARS
	SAPGUI Add-On for SilkPerformer

VUser Type	Application Type
	Oracle Applications/Forms Add-On PeopleSoft Add-On Siebel Add-On Citrix Add-On Terminal Emulation (Green-Screen) Add-On Tuxedo/ATMI Add-On

Known Issues in SilkPerformer

This list contains known issues in SilkPerformer and provides work-arounds where available:

General SilkPerformer Issues

Multi-byte character set support limitations

Problem:

The protocol / testing support of the Multi-Byte Character Set / UTF-8 / EUC-JP is limited to certain application types.

Resolution:

The protocol / testing support of the Multi-Byte Character Set / UTF-8 / EUC-JP is limited to the following application types:

- Web application testing, both protocol-level and browser-driven level
- SAPGUI testing
- Oracle Forms/Oracle Applications testing
- Citrix testing

.

ShopIt does not work on 64-bit operating systems

Problem:

After installing ShopIt on a 64-bit operating system, the application does not display in the browser.

Resolution:

On 64-bit systems, IIS requires that 32-bit applications be enabled. To do this, proceed as follows:

1. Open Internet Information Services (IIS) Manager.
2. Select **Application Pools**.
3. Right-click the application pool that you are using in IIS and choose **Advanced Settings**.
4. Set the option **Enable 32-Bit Applications** to `True`.

.

Optical character recognition (OCR) does not work for multibyte characters

Problem:

Optical character recognition (OCR) does not work for multibyte characters

Resolution:

Unfortunately there is no solution to this. SilkPerformer uses a third-party DLL for optical character recognition which only supports ASCII characters.

How can I get SilkPerformer "What's This" contextual Help to work on Windows Vista?

Problem:

How can I get SilkPerformer "What's This" contextual Help to work on Windows Vista?

Resolution:

In SilkPerformer it is possible to get information about GUI functionality by right-clicking GUI controls and choosing **What's This?**. This contextual help does not work on Windows Vista. This is a known issue related to the fact that the Windows Help program `winHlp32.exe` is no longer included with Windows Vista. To resolve this, a download for 32-bit .hlp files can be downloaded from the Microsoft Download Center. For more information, see: <http://support.microsoft.com/kb/917607>.

Performance Explorer Issues

How can I resolve the error 'Internal Error: MIB-File could not be compiled (check syntax)' when compiling a MIB in the Performance Explorer?

Problem:

How can I resolve the error `Internal Error: MIB-File could not be compiled (check syntax)` when compiling a MIB in the Performance Explorer?

Resolution:

The above error can occur in Performance Explorer when the MIB file you are trying to compile uses OIDs (Object Identifiers) which are declared after the module identity in the MIB file. Currently for Performance Explorer to compile a MIB, the OIDs have to be declared before the module identity. To work around this problem, edit the MIB in a text editor and move the OIDs so that they are declared before the module identity.

Snippet of JVM Management MIB File in which the enterprise OIDs have been cut from the MIB file and pasted before the module identity:

```
-- Enterprise OIDs
-----

--      internet          OBJECT IDENTIFIER ::= { iso(1) org(3) dod(6) 1 }
--      private           OBJECT IDENTIFIER ::= { internet 4 }
--      enterprises       OBJECT IDENTIFIER ::= { private 1 }
sun      OBJECT IDENTIFIER ::= { enterprises 42 }
products OBJECT IDENTIFIER ::= { sun 2 }
jmgmt    OBJECT IDENTIFIER ::= { products 145 }
-- experimental          OBJECT IDENTIFIER ::= { jmgmt 1 }
standard OBJECT IDENTIFIER ::= { jmgmt 3 }
jsr163   OBJECT IDENTIFIER ::= { standard 163 }
```

```
-- Module Identity
-----
jvmMgtMIB MODULE-IDENTITY
  LAST-UPDATED "200403041800Z"
  -- Format is "YYYYMMDDhhmmZ"
  ORGANIZATION "Sun Microsystems, Inc."
```

Graphics do not display when viewing an MHT overview report with Internet Explorer 7

Problem:

When an overview report is saved as MHT, images do not display when viewing the report with Internet Explorer 7.

Resolution:

View the report with Internet Explorer 6 or another browser.

Why am I unable to capture JMX measures during monitoring when using Performance Explorer?

Problem:

Why am I unable to capture JMX measures during monitoring when using Performance Explorer?

Resolution:

If this problem is affecting a Windows 2003 machine, it may be caused by the following known issue in SilkPerformer 2007 & 2008:

JMX Monitoring does not work on Windows 2003 servers that have Terminal Services installed (31679).

This is included in the Known Issues section of the Release Notes for SilkPerformer 2007 & 2008. It is caused by a defect in Eclipse (#171413). For further information see <https://bugs.eclipse.org/bugs/>.

There is no workaround for this issue other than to uninstall Terminal Services from the Windows 2003 machine.

TrueLog Explorer Issues

TrueLog Explorer input data customization does not work as expected with Windows Internet Explorer 9

Problem:

TrueLog Explorer input data customization displays graphic glitches and sometimes produces error messages when using Windows Internet Explorer 9.

Resolution:

Windows Internet Explorer 8 is recommended.

On-access virus scanner software may cause TrueLog Explorer to crash

Problem:

On-access virus scanner software may cause TrueLog Explorer to crash.

Resolution:

Virus scanner software may cause a variety of problems including TrueLog Explorer crashes or performance degradation. We recommend disabling virus scanner software on the agent computers and on the controller computer for the duration of load tests.

Visual script modifications fail if the related transaction is in an include file

Problem:

Visual script modifications fail if the related transaction is in an include file.

Resolution:

Do not move transactions to BDH files.

Visual user data customization does not work for browser-level scripts

Problem:

Visual user data customization does not work for browser-level scripts

Resolution:

This behavior is by design, as TrueLog Explorer only considers forms submitted by `WebPageSubmit` calls (page-based browser-level API), because the HTML form names are required to match HTML and BDL forms. If you want to customize your script using TrueLog Explorer Visual User Data Customization, you need to record a page-based browser-level API script.

SAPGUI Issues

Control position information cannot be retrieved correctly from SAP

Problem:

In rare instances, control position information can not be retrieved correctly from SAP. Therefore TrueLog Explorer might not be able to display the selected control rectangle at the correct position on the screenshot.

Resolution:

Use the control tree instead of the screenshot.

Citrix Issues

Citrix scripts run into timeout when UAC is turned on

Problem:

When recording or replaying Citrix scripts, a 30 second delay causes a timeout error. This delay only occurs when UAC is turned on.

Resolution:

Turn off UAC to successfully record and replay Citrix scripts.

Citrix scripts fail on Windows Server 2008 with Workbench error 'LoadtestController: 3317 - The virtual user's process terminated' with Citrix client software v10.2 or earlier

Problem:

Citrix scripts fail on Windows Server 2008 with Workbench error `LoadtestController: 3317 - The virtual user's process terminated` with Citrix client software v10.2 or earlier

Resolution:

Citrix XenApp Plugin 11.2 or later is recommended for SilkPerformer agents on Windows Server 2008, 2008R2, and Windows 7.

Citrix scripts fail on SilkPerformer agents running Windows Server 2008 R2 and Windows 7 with TrueLog error 'CitrixConnect(CitrixEngine: 6 - Connect failed, Connection timed out)' with Citrix client software v11.2 or later

Problem:

Citrix scripts fail on SilkPerformer agents running Windows Server 2008 R2 and Windows 7 with TrueLog error `CitrixConnect(CitrixEngine: 6 - Connect failed, Connection timed out)` with Citrix client software v11.2 or later

Resolution:

Use System Configuration Manager, **Applications** tab, to set a local account for the SilkPerformer agent.

Customizing CitrixKeyString input using multibyte characters sends corrupted input to the server

Problem:

Customizing `CitrixKeyString` input using multibyte characters sends corrupted input to the server.

Resolution:

When customizing input of `CitrixKeyString` functions, you are simulating keyboard input. For multibyte characters, you have to enter the phonetic transcription of the desired character. There is no point in entering a multibyte character directly, although the compiler will allow it if the codepage is set correctly.

Invalid CitrixKey function recorded for [hankaku/zenkaku] key

Problem

Invalid `CitrixKey` function recorded for [hankaku/zenkaku] key

Resolution

Assign a different shortcut for switching between input modes or use the mouse instead of a keyboard shortcut. See the Microsoft IME **Advanced Settings** dialog for details.

Connecting to existing session during Citrix recording results in unusable script

Problem:

Connecting to existing session during Citrix recording results in unusable script

Resolution:

When connecting to an existing Citrix session, the Citrix client does not recognize any windows and therefore no synchronization functions are scripted. You should always record a new session.

SilkPerformer crashes when generating font database for Citrix OCR on Windows 2003

Problem

SilkPerformer crashes when generating font database for Citrix OCR on Windows 2003.

Resolution

This behavior may occur when you have Data Execution Prevention (DEP) installed and configured to run for all programs and services.

DEP was introduced in Service Pack 2 for Windows XP and Service Pack 1 for Windows 2003. It is a set of hardware and software technologies that perform additional checks on memory to help prevent malicious code from running on a system. On occasion, users who have it enabled for all programs and services have found that it causes verifications to fail with the above error message being reported during execution of a Citrix BDF script.

To verify if DEP is causing the above error message, do the following:

1. Right-click **My Computer** and select **Properties**.
2. Click **Advanced**.
3. Click **Settings** in the **Performance** section.
4. Click **Data Execution Prevention**.

Ensure that the option button **Turn on DEP for essential windows programs and services only** is enabled before executing the BDF script and verifying that the error message is still reported.



Note: You will need to reboot your computer upon changing the DEP settings.

Oracle Forms Issues

After hooking into main Oracle Forms applet classes, JInitiator cannot load additional jar files that rely on those classes

Problem

After hooking into main Oracle Forms applet classes, JInitiator cannot load additional jar files that rely on those classes

Resolution

When recording Oracle Forms or Oracle Applications, define the following Java Runtime Options on the **JInitiator Properties** Dialog: `"-noverify -mx128m"` NoVerify prevents these loading issues. Additionally, the default **Virtual Memory Size** of JInitiator 1.1.7.x is between 16 and 64 MB. The option `-mx128m` increases the virtual memory size to 128MB. This additional memory is needed as there is some

extra memory overhead caused by recording. If you run into an `OutOfMemory` error you can further increase this value.

Browser crashes during recording of Oracle Forms

Problem

Browser crashes during recording of Oracle Forms.

Resolution

When recording Oracle Forms 6i it is recommended that you disable Java JIT (Just-In-Time compiling) in the Java Runtime settings. This is because the JIT library of the Java Virtual Machine (`symcjit.dll`) may crash your browser.

Java JIT can be disabled using one of the following options:

Option 1: Define - `DJAVA.COMPILER=NONE` in the Java runtime settings of the Oracle **JInitiator Properties** dialog. This must be done using the JInitiator control panel, which is installed with JInitiator (available in the Windows control panel).

1. Launch the JInitiator Control Panel.
2. Add `DJAVA.COMPILER=NONE` to the **Java Run Time Parameters** text field.
3. Click **Apply**.

Option 2: Use the check box on the Oracle JInitiator Properties dialog to disable the Just In Time Compiler (only available since version 1.1.8.x).

1. Launch the JInitiator Control Panel.
2. Select the **Advanced** tab.
3. Uncheck the **Enable Just In Time Compiler** checkbox.
4. Click **Apply**.

Option 3: Define environment variable: `JAVA_COMPILER=NONE`.

1. Right-click **My Computer** and choose **Properties**.
2. Choose **Advanced**.
3. Choose **Environment Variables**.
4. Under **System Variables** click **New**.
5. For **Variable Name** enter `JAVA_COMPILER`.
6. For **Variable Value** enter `NONE`.
7. Click **OK** to exit out of dialogs.

Web Issues

Recording of browser traffic does not work when browser window is already open.

Problem

Recording of browser traffic does not work when browser window is already open.

Resolution

Close all browser windows before recording a script.

Opera versions

Windows Internet Explorer 8 recorded scripts do not run with Windows Internet Explorer 9 (and vice versa)

Problem

Windows Internet Explorer 8 recorded scripts do not run with Windows Internet Explorer 9 (and vice versa).

Resolution

Run Windows Internet Explorer 8 recorded scripts using Windows Internet Explorer 8. Run Windows Internet Explorer 9 recorded scripts using Windows Internet Explorer 9.

Browser-Driven Load Testing Issues

Browser-Driven Load Testing IE compatibility

Problem

When Windows Internet Explorer (IE) 9.0 is installed, only the setting for IE7 Standard mode (7000) works correctly. The registry settings are correctly written, but not used by the IE-control inside SilkPerformer.

Resolution

There is no workaround available for this issue. However, when Windows Internet Explorer 8 is installed, IE8 and IE7 modes can be used.

Database Issues

SilkPerformer cuts last character of SQL statement

Problem

SilkPerformer cuts last character of SQL statement.

Resolution

The ODBC `dclsql` section requires a space or a carriage return after the last statement. If there is no white space after a SQL statement at the end of a script file, SilkPerformer will truncate the SQL statement (remove the last character).

Example

```
dclsql
...
order by p_lastname,p_zip; ! WHITE SPACE NEEDED HERE !
Space or Carriage Return required otherwise the following error occurs:
Error OdbcPrepare ODBC: 5 - ODBC error, S0022 (207): [Microsoft][ODBC SQL
```

```
Server Driver][SQL Server]Invalid column name "p_zi".
*** Virtual user stopped *** Severe API error (SEVERITY_PROCESS_EXIT)
```

Recorder generates non-compilable database script

Problem

Recorder generates non-compilable database script. For example, upon compiling database script you receive the error message `compile error LEX 18: /* comment is not closed before end of file.`

Resolution

This is currently a known issue in SilkPerformer. The problem occurs because the characters `/*` appear in a SQL comment in your script and because this character sequence is used for block comments. SilkPerformer expects to find a closing block comment sequence of `*/` in the script also. In order to resolve this, look for the `*/` sequence in a SQL comment in your script and remove both characters. As these are just comments they have no impact on testing. Below is an example of what a SQL comment with such characters may look like:

```
/**
  TMain_SQL004:
  insert into /
*my_person(p_no,p_opening,p_title,p_firstname,p_lastname,p_aline1,p_aline2,p_z
ip,p_district) values(?,? ,? ,?
,? ,? ,? ,? ,? );
***/
```

Alternatively there is a setting in SilkPerformer to stop SQL comments from being scripted. To do this go to **Settings > Active Profile > Record > Script > Protocols** and uncheck the **SQL Comment** checkbox.

Remote agents unable to replay OCI 8 script

Problem

When recording an OCI 8 application that writes LOB data into the database, the Recorder generates files into the project directory that store these data in order to have these data available during replay. These files are named like `LOB_XXXXXXXXX.dat`. However the files will not be available during replay on remote agents and therefore cause replay errors.

Resolution

Manually add the generated DAT files to the `Data Files` section of the project in order to run the script on remote agents.

OCI replay engine generates error when replaying database script

Problem

If a SQL statement contains a comment in the notation beginning with `--` then the OCI replay engine generates an error showing a misleading error message. This is caused because the recorder removes line breaks from the SQL statement string if the profile setting **Record > Script > Protocols > Trim SQL** is enabled.

Resolution

Either find the end of the comment text and insert a line break in the statement string of the `declsql` section of the script or disable the setting **Record > Script > Protocols > Trim SQL** and re-record the application.

Faulty SQL statement may be generated in recorded script if multibyte characters are included

Problem

Faulty SQL statement may be generated in recorded script if multibyte characters are included.

Resolution

Manually adjust the SQL statement in the script.

GUI-Level Testing Support

Connection attempt times out when invalid login credentials are provided (no error message provided)

Problem

Connection attempt times out when invalid login credentials are provided. No error message is provided to offer direction.

Resolution

Valid login credentials must be provided.

Resolved Issues

The following issues have been resolved in SilkPerformer 2011:

Issue #	Description	Notes
RPI 1079223	The <code>nTimeout</code> parameter of the <code>BrowserFind</code> function is not working as designed.	
RPI 1079128	The <code>perfrun</code> process crashes when using the <code>FormatDateTime</code> sample code from the Help.	A superfluous space character in the sample code was removed.
RPI 1078611	Some browser-driven Web load testing functions (<code>BrowserClick</code> , <code>BrowserLinkSelect</code>) may throw an error although the action is successful.	
RPI 1078461	SilkPerformer's default cipher might not match SSL server's requirement after OpenSSL change.	
RPI 1078312	The <code>OraFormsGetPropStringArray</code> function requires the control's ID rather than a string as described in the Help.	The <code>OraFormsGetPropStringArray</code> function actually accepts both a control's name (string) or its ID. Some controls however have no declared name, in which case you must provide the ID.
RPI 1077865	SilkPerformer's SAP eCATT connection dialog has a username / password character limit which does not exist in SAPLogon.	
RPI 1077832	Remote installation of SilkPerformer fails without <code>MSVCR100.dll</code> .	
RPI 1077626	The Run button is disabled for the all-day workload.	
RPI 1077544	SilkPerformer's browser-driven Web Load testing feature does not support Win32-based popup dialogs.	
RPI 1077497	Using SilkPerformer's Browser Application with a Greek locale, typing Greek characters with the keyboard results in wrong characters entered into the application.	
RPI 1076813	Using the <code>FileGetCol</code> function, when specifying an <code>nMaxLen</code> value that is less than the maximum length of the column value, SilkPerformer	SilkPerformer now reports a warning and returns the truncated string correctly.

Issue #	Description	Notes
	<p>reports an error "RESERR: 180 - Buffer passed to function <FileGetCol> is too small to hold data".</p>	
RPI 1072961	<p>Replaying a script against an NTLM-authenticated server via a proxy does not work.</p>	
RPI 583831	<p>Browser-driven Web load testing: Under certain circumstances (timing issue), the operation that deletes the virtual user's cache and cookies starts at the wrong location, which may lead to a non-operational Windows operating system.</p>	
RPI 582871	<p>Realtime Measures do not work for agents connected through a proxy.</p>	
RPI 579986	<p>"Compile new Mib..." crashes on 64-bit operating systems.</p>	

End of Support

Please note that the following technologies have been deprecated and are no longer supported in this version of SilkPerformer:

- Several deprecated technologies have been removed from the list of pre-defined monitoring data sources in Performance Explorer.
- WAP browsers and gateways, including Opera, Nokia, Phone.Com, OpenWave, WAP Lite, and others
- Microsoft Visual Studio 2005
- Streaming media, including Microsoft Media Player and RealNetworks players
- COM and COM+ support

Navigate to supportline.microfocus.com for further assistance from Customer Care.